

## Surface Mount Multilayer Ceramic Chip Capacitors for Commercial Applications



### FEATURES

- C0G is an ultra-stable dielectric offering a Temperature Coefficient of Capacitance (TCC) of  $0 \pm 30$  ppm/°C
- Low Dissipation Factor (DF)
- Ideal for critical timing and tuning applications
- Ideal for snubber and surge suppression applications
- Surface mount, precious metal technology, wet build process
- Halogen-free according to IEC 61249-2-21



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### ELECTRICAL SPECIFICATIONS

**Note:** Electrical characteristics at + 25 °C unless otherwise specified

**Operating Temperature:** - 55 °C to + 150 °C

**Capacitance Range:** 1.0 pF to 0.056  $\mu$ F

**Voltage Rating:** 10 Vdc to 1000 Vdc

**Temperature Coefficient of Capacitance (TCC):**  
 $0 \pm 30$  ppm/°C from - 55 °C to + 125 °C

**Dissipation Factor (DF):**  
0.1 % maximum at 1.0  $V_{rms}$  and 1 kHz for values > 1000 pF  
0.1 % maximum at 1.0  $V_{rms}$  and 1 MHz for values  $\leq$  1000 pF

**Aging Rate:** 0 % maximum per decade

### Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 M $\Omega$  minimum or 1000  $\Omega$ F, whichever is less

At + 125 °C and rated voltage 10 000 M $\Omega$  minimum or 100  $\Omega$ F, whichever is less

### Dielectric Withstanding Voltage (DWV):

This is the maximum voltage the capacitors are tested for a 1 to 5 second period and the charge/discharge current does not exceed 50 mA

$\leq$  200 Vdc : DWV at 250 % of rated voltage

500 Vdc: DWV at 200 % of rated voltage

630/1000 Vdc: DWV at 150 % of rated voltage

### ORDERING INFORMATION

VJ0805	A	102	K	X	A	A	T	### (2)(4)
CASE CODE	DIELECTRIC	CAPACITANCE NOMINAL CODE	CAPACITANCE TOLERANCE	TERMINATION	DC VOLTAGE RATING (1)	MARKING	PACKAGING	PROCESS CODE
0402 0603 0805 1206 1210 1808 1812 1825 2220 2225	A = C0G (NP0)	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. An "R" indicates a decimal point. <b>Examples:</b> 102 = 1000 pF 1R8 = 1.8 pF	B = $\pm$ 0.10 pF C = $\pm$ 0.25 pF D = $\pm$ 0.5 pF F = $\pm$ 1 % G = $\pm$ 2 % J = $\pm$ 5 % K = $\pm$ 10 % <b>Note:</b> B, C, D < 10 pF F, G, J, K $\geq$ 10 pF	X = Ni barrier 100 % tin plate matte finish F = AgPd B = Polymer 100 % tin plate matte finish (5)	X = 25 V A = 50 V B = 100 V C = 200 V E = 500 V L = 630 V G = 1000 V	A = Unmarked M = Marked <b>Note:</b> Marking is only available for 0805 and 1206 with termination code "X"	T = 7" reel/plastic tape C = 7" reel/paper tape R = 11 1/4" reel/plastic tape P = 11 1/4" reel/paper tape O = 7" reel/flamed paper tape I = 11 1/4"/13" reel/flamed paper tape <b>Note:</b> "I" and "O" is used for "F" termination paper taped size 0402/0603/0805	

#### Notes:

(1) DC voltage rating should not be exceeded in application

(2) Process Code may be added with up to three digits, used to control non-standard products and/or special requirements

(3) Case size designator may be replaced by a four digit drawing number used to control non-standard products and/or requirements

(4) "A2" temporarily used to identify manufacturing plant for size  $\geq$  1812


(5) Selected values available, contact [mlcc@vishay.com](mailto:mlcc@vishay.com) for list of released ratings



# VJ C0G (NP0) Dielectric

Surface Mount Multilayer Ceramic Chip Capacitors Vishay Vitramon  
for Commercial Applications

## DIMENSIONS in inches [millimeters]



EIA STYLE	PART ORDERING NUMBER	LENGTH (L)	WIDTH (W)	MAXIMUM THICKNESS (T)	TERMINATION (P)	
					MINIMUM	MAXIMUM
0402	VJ0402	0.040 + 0.004/- 0.002 [1.00 + 0.10/- 0.05]	0.020 + 0.004/- 0.002 [0.50 + 0.10/- 0.05]	0.024 [0.60]	0.004 [0.10]	0.016 [0.41]
0603	VJ0603	0.063 ± 0.005 [1.60 ± 0.12]	0.031 ± 0.005 [0.80 ± 0.12]	0.037 [0.94]	0.012 [0.30]	0.018 [0.46]
0805	VJ0805	0.079 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.057 [1.45]	0.010 [0.25]	0.028 [0.71]
1206	VJ1206	0.126 ± 0.008 [3.20 ± 0.20]	0.063 ± 0.008 [1.60 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
1210	VJ1210	0.126 ± 0.008 [3.20 ± 0.20]	0.098 ± 0.008 [2.50 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
-	VJ1808	0.177 ± 0.010 [4.50 ± 0.25]	0.080 ± 0.010 [2.03 ± 0.25]	0.067 [1.70]	0.010 [0.25]	0.030 [0.76]
1812	VJ1812	0.177 ± 0.010 [4.50 ± 0.25]	0.126 ± 0.008 [3.20 ± 0.20]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
1825	VJ1825	0.177 ± 0.010 [4.50 ± 0.25]	0.252 ± 0.010 [6.40 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2220	0.220 ± 0.008 [5.59 ± 0.20]	0.200 ± 0.010 [5.08 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2225	0.220 ± 0.010 [5.59 ± 0.25]	0.250 ± 0.010 [6.35 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]

**Note:**

- Polymer terminations, "B" termination part number code, length dimensions, positive tolerances (including band width) above are allowed to increase by the following amounts:  
0402/0603 size, consult [mlcc@vishay.com](mailto:mlcc@vishay.com)  
0805/1210/1812/2220/2225 max. add length 0.0040"/0.10 mm  
1206/1808 max. add length 0.0055"/0.14 mm

# VJ COG (NP0) Dielectric



Vishay Vitramon Surface Mount Multilayer Ceramic Chip Capacitors  
for Commercial Applications

SELECTION CHART																					
DIELECTRIC		COG (NP0)																			
STYLE		VJ0402			VJ0603			VJ0805				VJ1206					VJ1210 <sup>(1)</sup>				
EIA TYPE		0402			0603			0805				1206					1210				
VOLTAGE (Vdc)		25	50	100	50	100	200	50	100	200	500	50	100	200	500	630	50	100	200	500	630
CAP. CODE	CAP.																				
1R0	1.0 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
1R2	1.2 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
1R5	1.5 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
1R8	1.8 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
2R2	2.2 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
2R7	2.7 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
3R3	3.3 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
3R9	3.9 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
4R7	4.7 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
5R6	5.6 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
6R8	6.8 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
8R2	8.2 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**					
100	10 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
120	12 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
150	15 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
180	18 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
220	22 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
270	27 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
330	33 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
390	39 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
470	47 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	
560	56 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	*
680	68 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	*
820	82 pF	**	**	**	**	**	**	**	**	**	**	**	**	**	**	**				*	*
101	100 pF	**	**	**	**	**	**	**	**	**	**	*	*	*	*	*				*	*
121	120 pF	**	**	**	**	**	**	**	**	**	**	*	*	*	*	*				*	*
151	150 pF	**	**		**	**	**	**	**	**	**	*	*	*	*	*				*	*
181	180 pF	**	**		**	**	*	**	**	**	**	*	*	*	*	*				*	*
221	220 pF	**	**		**	**	*	**	**	**	*	*	*	*	*	*				*	*
271	270 pF				**	**	*	**	**	**	*	*	*	*	*	*				*	*
331	330 pF				**	**		**	**	**	*	*	*	*	*	*				*	*
391	390 pF				**	**		**	**	**	*	*	*	*	*	*				*	*
471	470 pF				**	**		**	**	*	*	*	*	*	*	*				*	*
561	560 pF				**	**	*	**	**	*	*	*	*	*	*	*				*	*
681	680 pF				**	**	*	**	**	*	*	*	*	*	*	*				*	*
821	820 pF			*	**	**	*	**	**	*	*	*	*	*	*	*				*	*
102	1000 pF							**	**			*	*	*	*	*				*	*
122	1200 pF							**	*			*	*	*	*	*				*	*
152	1500 pF							**	*			*	*	*	*	*				*	*
182	1800 pF							**	*			*	*	*	*	*				*	*
222	2200 pF							*	*			*	*	*	*	*				*	*
272	2700 pF							*	*			*	*	*	*	*				*	*
332	3300 pF							*	*			*	*	*	*	*				*	*
392	3900 pF							*	*			*	*	*	*	*				*	*
472	4700 pF							*	*			*	*	*	*	*				*	*
562	5600 pF							*	*			*	*	*	*	*				*	*
682	6800 pF							*	*			*	*	*	*	*				*	*
822	8200 pF							*	*			*	*	*	*	*				*	*
103	0.010 μF											*	*	*	*	*				*	*
123	0.012 μF											*	*	*	*	*				*	*
153	0.015 μF											*	*	*	*	*				*	*
183	0.018 μF											*	*	*	*	*				*	*
223	0.022 μF											*	*	*	*	*				*	*
273	0.027 μF											*	*	*	*	*				*	*
333	0.033 μF											*	*	*	*	*				*	*
393	0.039 μF											*	*	*	*	*				*	*
473	0.047 μF											*	*	*	*	*				*	*
563	0.056 μF											*	*	*	*	*				*	*

**Note:**

<sup>(1)</sup> See soldering recommendations within this data book, or visit [www.vishay.com/doc?45034](http://www.vishay.com/doc?45034)

\*\* Paper tape • Plastic tape



# VJ C0G (NP0) Dielectric

Surface Mount Multilayer Ceramic Chip Capacitors Vishay Vitramon  
for Commercial Applications

SELECTION CHART																								
DIELECTRIC		C0G (NP0)																						
STYLE		VJ1808 <sup>(1)</sup>					VJ1812 <sup>(1)</sup>					VJ1825 <sup>(1)</sup>				VJ2220 <sup>(1)</sup>					VJ2225 <sup>(1)</sup>			
EIA TYPE		-					1812					1825				-					-			
VOLTAGE (Vdc)		50	100	200	500	1000	50	100	200	500	1000	50	100	200	500	50	100	200	500	1000	50	100	200	500
CAP. CODE	CAP.																							
1R0	1.0 pF																							
1R2	1.2 pF																							
1R5	1.5 pF																							
1R8	1.8 pF																							
2R2	2.2 pF																							
2R7	2.7 pF																							
3R3	3.3 pF																							
3R9	3.9 pF																							
4R7	4.7 pF																							
5R6	5.6 pF																							
6R8	6.8 pF																							
8R2	8.2 pF																							
100	10 pF																							
120	12 pF																							
150	15 pF																							
180	18 pF																							
220	22 pF																							
270	27 pF																							
330	33 pF																							
390	39 pF																							
470	47 pF																							
560	56 pF																							
680	68 pF																							
820	82 pF																							
101	100 pF																							
121	120 pF																							
151	150 pF																							
181	180 pF																							
221	220 pF																							
271	270 pF																							
331	330 pF																							
391	390 pF																							
471	470 pF																							
561	560 pF																							
681	680 pF																							
821	820 pF																							
102	1000 pF																							
122	1200 pF																							
152	1500 pF																							
182	1800 pF																							
222	2200 pF																							
272	2700 pF																							
332	3300 pF																							
392	3900 pF																							
472	4700 pF																							
562	5600 pF																							
682	6800 pF																							
822	8200 pF																							
103	0.010 μF																							
123	0.012 μF																							
153	0.015 μF																							
183	0.018 μF																							
223	0.022 μF																							
273	0.027 μF																							
333	0.033 μF																							
393	0.039 μF																							
473	0.047 μF																							
563	0.056 μF																							

**Note:**

<sup>(1)</sup> See soldering recommendations within this data book, or visit [www.vishay.com/doc?45034](http://www.vishay.com/doc?45034)  
• Plastic tape


# VJ C0G (NP0) Dielectric




Vishay Vitramon Surface Mount Multilayer Ceramic Chip Capacitors  
for Commercial Applications

## C0G (NP0) DIELECTRIC - TYPICAL PARAMETERS


TYPICAL PARAMETER C0G (NP0)  
TEMPERATURE COEFFICIENT OF CAPACITANCE




TYPICAL PARAMETER C0G (NP0)  
VOLTAGE COEFFICIENT OF CAPACITANCE




TYPICAL PARAMETER C0G (NP0)  
AGING RATE




TYPICAL PARAMETER C0G (NP0)  
MINIMUM INSULATION  
RESISTANCE VS. TEMPERATURE



TYPICAL PARAMETER C0G (NP0)  
CHANGE OF CAPACITANCE WITH FREQUENCY



TYPICAL PARAMETER C0G (NP0)  
CHANGE OF CAPACITANCE WITH FREQUENCY





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.